



## Application & Functionality

- Interfaces the Geo-Sense VHR single channel mini-streamers to any Third Party recording system
- Provides high quality analogue frequency filters and two-stage analogue gain

### Analogue Frequency Filtering

There are four settings for analogue filtering:

- 1) bandpass filter of 80 Hz - 2.5 kHz,
- This is usually the best setting for the sparker spectrum. Other filter settings can be provided.
- 2) high-pass (low-cut) filter of 80 Hz
- To remove low frequency noise, it is usually sufficient to filter only the low frequencies, which are difficult to remove digitally.
- 3) low-pass (high-cut) filter of 2.5 kHz
- To cut out the high frequencies.
- 4) no filter

### Analogue Gain

To minimise distortion and to avoid saturation, the seismic signal is amplified in two stages:

- 1) 0-6-12-18 dB (four levels), the first stage gain is applied after the high-pass filter;
- 2) 0-6-12-18 dB (four levels), the second stage gain is applied after the low-pass filter.

By using the maximum gain setting for both stages, you can achieve a total amplification of 36 dB.

## Operational Features

- Dedicated 4-pin connection to power the pre-amplifier of the Geo-Sense streamer and to receive the signal
- Standard BNC connections for signal output to any seismic recorder and signal input from any Third Party streamer
- Audio output to headphone on front panel
- Mains power 110-230 V AC / 50-60 Hz

## General Features

The Geo-Sense filter/gain interface is designed to operate with the Geo-Sense mini-streamers and allows the Geo-Sense mini-streamers to be used with ANY digital recording system.

The interface is also designed to accept signal input, via BNC cable, from any other type of streamer.

It is a stand-alone unit that applies high quality, non-distorting analogue filters and two-stage gains to a single-channel seismic signal.

If you are working with a seismic recording system that has no suitable analogue front-end, then the Geo-Sense filter/gain interface would be an essential part of your system.

## Audio Control

You can now listen to your streamer using a headphone connected to the audio socket on the front panel.






## Technical Data & Schematics

### Filter & Gain Parameters

First stage	Switchable high-pass (low-cut) filter / 80 Hz 4th order
Second stage	Switchable amplifier / 0-6-12-18 dB
Third stage	Switchable low-pass (high-cut) filter / 2.5 kHz 4th order
Fourth stage	Switchable amplifier / 0-6 -12-18 dB



### Dedicated Geo-Sense Streamer Connection

The 4-pin connection is used for both the signal input from the streamer and the 12 V DC power supply to the streamer's internal pre-amplifier. This power supply replaces the standard battery box (which is normally also provided with the mini-streamer).

The four pins are assigned as follows:

- Pin 1 +12 V DC power to pre-amplifier
- Pin 2 Ground shield (earth)
- Pin 3 Positive (+) signal from pre-amplifier
- Pin 4 Ground signal from pre-amplifier

### BNC Input and Output

The two BNC connections at the rear of the unit are for the single-ended input from the streamer, and the signal output to any digital recorder (with four settings for signal level voltage peak to peak of 0.3, 1, 3 and 10 V).

### Optional Functions

- Customised filter settings are available on request.